



27325-87
(5091-85)

27325-87

Elements and products of wood and wood materials. (CT)
Method for determination of paint coatings adhesion

5091—85)

5609

01.01.89

01.01.94

2)

(1)

(-)

1.

1.1.

10

50X50

70%).

1.2.

(20±2) °

3 ,

(55—
2

(23±3)°

(50±5) %,

2.

50 , 2500 ; (19,8±0,1),
 50—60 ; (20+0) ; ,
 , ;
 5 6456—82;
 2768—84;
 11109—74; , ;

3.

3.1.

5 , (), —

3.2.

, , 1—

2

3.3.

, (24),

(20±2)° .

3.4.

,

3.5.

1

,

,

4.

4.1.

1

2

1 1

			4			
		1			s	
			025			

fP

7—3— , 2— ,

4.2. 1 (40—50) /

2

(60+30)

4 3.

1.

5.

5.1. ()

S_{0T} — , S_{0T} = $\frac{\pi d^2}{4} = 314 \text{ mm}^2$

d — , 20 .

5.2.

10. (.) , ,
, 50%, (. 2).

1

—

—

—

—

()

(

).

().

—

— , — , ,

,

(,)

(), -----

()

,

:

()

1 (2)

	, ,	, ,	,	%
1				
2				
3				

1.

, . , . ; , . , . ; , . , . ;
- , . , . ; , . , . ;
- , . , . ; , . , . ;

2.**17.06.87 2106****3.****5091—85.****1.****4624—78****4.**

2768—84	2
6456—82	2
11109—74	2

10 000	07 07 87	24 08 87 0 5	0 5	0 31	3
	«	»	»	, 123840, , , 6 , 954	, 3